



068

LONDON[®] BALL VALVE, FULL FLOW





Female/female threads
T handle in aluminium
 Body in nickel-plated brass
 Minimum and maximum working temperatures:
 -20°C, 60°C (class T2 under EN331).
 Threads: ISO 7/1 Rp parallel
 (equivalent to DIN EN 10226-1 and BS21)

SIZE	1/4"	3/8"	1/2"	3/4"	1"
A (mm)	49.5	52.4	61	68	85
B (mm)	23.5	24	30.5	37	45.5
C (mm)	36.5	36.5	44.3	47.3	51.3
D (mm)	47	47	54	62	62
CH (mm)	18	21	25	31	38
WORKING PRESSURE Kg/cm ² bar	5	5	5	5	5
WORKING PRESSURE psi	72.5	72.5	72.5	72.5	72.5

069

LONDON[®] BALL VALVE, FULL FLOW



Male/female threads
T handle in aluminium
 Body in nickel-plated brass
 Minimum and maximum working temperatures:
 -20°C, 60°C (class T2 under EN331).
 Female thread: ISO 7/1 Rp parallel
 (equivalent to DIN EN 10226-1 and BS21)
 Male thread: ISO 7/1 R taper
 (equivalent to DIN EN 10226-1 and BS21)

SIZE	1/4"	3/8"	1/2"	3/4"	1"
A (mm)	56.9	58.9	68	75.5	90.5
B (mm)	23.5	24	30.5	37	45.5
C (mm)	36.5	36.5	44.3	47.3	51.3
D (mm)	47	47	54	62	62
CH (mm)	18	21	25	31	38
WORKING PRESSURE Kg/cm ² bar	5	5	5	5	5
WORKING PRESSURE psi	72.5	72.5	72.5	72.5	72.5



ART. 068-069