



072

BERLIN® BALL VALVE, FULL FLOW





Female/female threads
T handle in aluminium
 Body in nickel-plated brass
 Minimum and maximum working temperatures:
 -20°C, 60°C (class T2 under EN331).
 Threads: ISO 7/1 Rp parallel
 (equivalent to DIN EN 10226-1 and BS21)

SIZE	1/2"	3/4"	1"
A (mm)	75	80	90
B (mm)	32.5	42	49.5
C (mm)	47	49	52
D (mm)	54	62	62
CH (mm)	25	31	40
WORKING PRESSURE Kg/cm ² bar	5	5	5
WORKING PRESSURE PSI	72.5	72.5	72.5

073

BERLIN® BALL VALVE, FULL FLOW



Male/female threads
T handle in aluminium
 Body in nickel-plated brass
 Minimum and maximum working temperatures:
 -20°C, 60°C (class T2 under EN331).
 Female thread: ISO 7/1 Rp parallel
 (equivalent to DIN EN 10226-1 and BS21)
 Male thread: ISO 7/1 R taper
 (equivalent to DIN EN 10226-1 and BS21)

SIZE	1/2"	3/4"	1"
A (mm)	76.5	83.5	93
B (mm)	32.5	42	49.5
C (mm)	47	49	52
D (mm)	54	62	62
CH (mm)	25	31	40
WORKING PRESSURE Kg/cm ² bar	5	5	5
WORKING PRESSURE PSI	72.5	72.5	72.5

						ART. 072-073		ART. 073