



# ANTI SEIZE COMPOUND

Copper based anti seize paste for all static fasteners and mechanisms.  
Anti Seize Compound is an assembly and anti seize lubricant that prevents pick up and seizure even in wet, dirty and corrosive conditions.

## FEATURES

- Ø Temperature range  $-10^{\circ}\text{C}$  to  $1100^{\circ}\text{C}$
- Ø Prevents pick up and seizure of static threaded fasteners
- Ø Lubricates, protects and eases dismantling
- Ø Effective even in the most aggressive environments
- Ø Insoluble in water
- Ø Ideal for furnaces, exhaust systems, dockside and oil rig applications

## DIRECTIONS FOR USE

- Ø Apply as a thin film by brushing or wiping onto a clean dry surface.
- Ø For best results apply to both the male and female parts.

### Technical and Safety Data Sheets are available from:

**Fax Back Facility** : +44 (0)113 232 2770  
**Web Site** : [www.rocol.com](http://www.rocol.com)  
**Customer Service** : +44 (0)113 232 2700

Issue 1403d: 09/06/03

### **ROCOL Lubricants**

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

[www.rocol.com](http://www.rocol.com)

[www.rocolshop.com](http://www.rocolshop.com)

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers.  
There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.



# ANTI SEIZE COMPOUND

## TECHNICAL DATA (typical values)

Appearance	Dark coppery coloured paste
NLGI No. (IP 50)(ASTM D217)	NLGI No. 1/2
Base type	Mineral oil
Thickener	Organically modified clay
Solids	Copper, Graphite, MoS <sup>2</sup>
Solids content	Approximately 37%
Temperature range	-10 <sup>0</sup> C to 1100 <sup>0</sup> C
Water solubility	Insoluble
Approximate coverage	5m <sup>2</sup> /kg
Specifications	
Naval Cat No	0475-541-8659 (6kg)
RAF ref No	34D/301-6210 (85g) 34D/224-6794 (500g)
NATO Stock No	8030-99-301-6210 (85g) 8030-99-224-6794 (500g) 8030-99-541-8659 (6kg)
Storage	Storage temperature should be controlled to between 1 and 40 °C.
Pack sizes	85g, 500g, 6kg, 18kg

Issue 1403d: 09/06/03

2

### ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

[www.rocol.com](http://www.rocol.com)

[www.rocolshop.com](http://www.rocolshop.com)

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

TECHNICAL DATA