



## TECHNICAL DATA

# GLASSFLO 7070

Biodegradable Gob Shear Lubricant

TECHNICAL DATA

### Description

ROCOL Glassflo 7070 is a specially formulated gob shear lubricant for use in the shear spray systems of automatic gob feeders. ROCOL Glassflo 7070 does not contain mineral oil, silicone, nitrites or phosphates and is completely biodegradable. It forms a stable emulsion when mixed with water and provides lubrication and cooling of shear blades, guide tubes and delivery chutes.

### Outstanding Features

- **Excellent shear blade lubrication and cooling**
- **Controlled gob speed and accuracy of delivery**
- **Increase shear blade life**
- **Compatible with copper, aluminium and polycarbonates**

### Directions for use

ROCOL Glassflo 7070 can be metered directly into the water spray line or pre-mixed on a batch basis to form a clear stable solution. Recommended dilution ratio is up to 200:1 with water, dependent upon operating conditions. ROCOL Glassflo 7070 should be applied directly to the shear blades, guide tubes and delivery chutes.

### ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: 0113 232 2600 Fax: 0113 232 2760

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW inc

The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason the information in this publication is given without responsibility

## Technical Data (typical values)

<i>Appearance:</i>	<i>Light brown translucent concentrate forming a clear stable solution when mixed with water.</i>
<i>Base Fluid:</i>	<i>Synthetic</i>
<i>Specific Gravity:</i>	<i>1.06</i>
<i>pH neat:</i>	<i>8.6</i>
<i>Odour</i>	<i>Slight Odour</i>
<i>Storage:</i>	<i>Storage at 0°C to 40°C. Do not allow to freeze.</i>

## Pack sizes and part codes

200 litre      part code 78909

## Health and Safety

Health and Safety information (COSHH, MSDS) is available from the Customer Service Department, ROCOL Lubricants., ROCOL House, Swillington, Leeds, LS26 8BS, England.

**Telephone:** 0113 232 2700, (When calling from outside UK: 44 113 232 2700).

**Fax:** 0113 232 2760, (When faxing from outside UK: 44 113 232 2760).

Issue:    Glassflo 7070 TDS 78909  
Date:     Nov-04

### ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: 0113 232 2600 Fax: 0113 232 2760

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW inc

The information in this publication is based on our experience and reports from customers.  
There are many factors outside our control and knowledge which effect the use and performance of our products  
for which reason the information in this publication is given without responsibility

TECHNICAL DATA