



TECHNICAL DATA
ULTRAFORM 1060
High Performance Fast Drying
Cold Metal Forming Lubricant

TECHNICAL DATA

Description

ROCOL ULTRAFORM 1060 is a high performance, fast drying cold metal forming lubricant, specially suitable for use with a wide range of ferrous and non-ferrous metals, including a range of galvanized and zintec coated steels. ROCOL ULTRAFORM 1060 contains extreme pressure additives which prevent metal pick up between the work piece and tool and provide a cost effective route to increased production rates.

ROCOL ULTRAFORM 1060 works as a vanishing film, eliminating the need to degrease components in some circumstances.

Outstanding Features

- **Minimises “slug pulling” on thin gauge materials**
- **Vanishing film**
- **Reduces metal pick up and scoring**
- **Easily cleaned**

Directions for use

ROCOL ULTRAFORM 1060 may be applied by brush, drip, roller, airspray, or airless spray systems. Where absolute freedom from surface discolouration is essential, it is recommended that compatibility trials are performed.

Technical Data (typical values)

<i>Appearance:</i>	<i>Colourless liquid</i>
<i>Odour:</i>	<i>Mild</i>
<i>Kinematic viscosity:</i>	<i>2.0 cSt at 25°C</i>
<i>Density at 20°C:</i>	<i>0.77 g/cm³</i>
<i>Storage:</i>	<i>Store at normal ambient temperature (5 to 30°C)</i>

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: 0113 232 2600 Fax: 0113 232 2760

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW inc

The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason the information in this publication is given without responsibility

Pack sizes and part codes

20 ltr part code 86213
200 ltr part code 86219

Health and Safety

Safety data sheet is available from the Customer Service Department, ROCOL Lubricants., ROCOL House, Swillington, Leeds, LS26 8BS, England.

Telephone: 0113 232 2700, (When calling from outside UK: 44 113 232 2700).

Fax: 0113 232 2760, (When faxing from outside UK: 44 113 232 2760).

Issue: Ultraform 1060 TDS 8621
Date: Jan-04

TECHNICAL DATA

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: 0113 232 2600 Fax: 0113 232 2760

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW inc

The information in this publication is based on our experience and reports from customers.

There are many factors outside our control and knowledge which effect the use and performance of our products for which reason the information in this publication is given without responsibility