



TECHNICAL DATA

ULTRAFORM 2010

High Performance, Extreme Pressure,
Cold Metal Forming Lubricant

TECHNICAL DATA

Description

ROCOL ULTRAFORM 2010 is a high performance, extreme pressure cold metal forming lubricant formulated for the most severe forming operations on heavy gauge ferrous metals.

ROCOL ULTRAFORM 2010 contains extreme pressure additives to prevent metal pick up between the work piece and tool and provide a cost effective route to increased production rates.

ROCOL ULTRAFORM 2010 can be used neat or diluted with water or mineral oil to the particular application.

Outstanding Features

- **Superior load carrying characteristics reduce metal pick up and scoring**
- **Suitable for use with carbide tooling**
- **Can be used neat or diluted with water or mineral oil**
- **Easily cleaned**

Directions for use

ROCOL ULTRAFORM 2010 may be applied by brush, drip, roller, aerospray, or airless spray systems, it is not recommended for use in re-circulating systems.

DILUTION WITH OIL: ROCOL ULTRAFORM 2010 should be diluted with mineral oil by adding the oil to the concentrate, whilst stirring continuously.

DILUTION WITH WATER: ROCOL ULTRAFORM 2010 can be used at dilutions of up to 5:1 depending on the severity of operation. Add concentrate to water at the recommended dilution, whilst stirring continuously. The emulsion must be continually agitated or re-mixed during use.

Where absolute freedom from surface discolouration is essential, it is recommended that compatibility trials are performed.

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: 0113 232 2600 Fax: 0113 232 2760

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW inc

The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason the information in this publication is given without responsibility

Technical Data (typical values)

<i>Appearance:</i>	<i>Viscous brown liquid</i>
<i>Odour:</i>	<i>Mild</i>
<i>Kinematic viscosity:</i>	<i>1500 cSt at 25°C</i>
<i>pH:</i>	<i>8.2 at 10:1</i>
<i>Density at 20°C:</i>	<i>1.17 g/cm³</i>
<i>Storage:</i>	<i>Store at normal ambient temperature (5 to 30°C)</i>

Pack sizes and part codes

20 ltr	part code 86043
200 ltr	part code 86049

Health and Safety

Safety data sheet is available from the Customer Service Department, ROCOL Lubricants, ROCOL House, Swillington, Leeds, LS26 8BS, England.

Telephone: 0113 232 2700, (When calling from outside UK: 44 113 232 2700).

Fax: 0113 232 2760, (When faxing from outside UK: 44 113 232 2760).

Issue: Ultraform 2010 TDS 8604

Date: Jan-04

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: 0113 232 2600 Fax: 0113 232 2760

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW inc

The information in this publication is based on our experience and reports from customers.
There are many factors outside our control and knowledge which effect the use and performance of our products
for which reason the information in this publication is given without responsibility

TECHNICAL DATA