

DGO series - Large - Rubber hose



Technical characteristics

Technology: Pipe locked with ratchet stop

Max operating pressure: 12 bar

Construction: Epoxy-coated steel case

Connection: 1 m of inlet supply hose

Equipped with: Fixed bracket

Fixed bracket


Inlet: G 3/8 F

Inlet: G 1/2 M for DGO 1320 + DGO 1610

+ 1 m hose

Pressure: 12 bar

Temperature: -15°C to +65°C

	A (mm)	B (mm)	C (mm)	ID/OD (mm)	Length (m)	Coupler	Flow rate (l/min)	Swivel inlet (BSPP)	Weight (kg)	Parts Numbers
	485	475	237	16 x 23	10	ISG 11	3000	G 1/2 M	25	DGO 1610
	485	475	237	10 x 17	25	ESI 07	500	G 3/8 F	26	DGO 1025ES
	485	475	237	13 x 20	20	ESI 07	1000	G 1/2 M	27	DGO 1320ES
	485	475	237	16 x 23	10	ESI 11	3000	G 1/2 M	27	DGO 1610ES
	485	475	237	10 x 17	25	ISI 06	500	G 3/8 F	26	DGO 1025IS
	485	475	237	13 x 20	20	ISI 08	1000	G 1/2 M	27	DGO 1320IS
	485	475	237	16 x 23	10	ISI 11	3000	G 1/2 M	25	DGO 1610IS
	485	475	237	10 x 17	25	CSI 06	500	G 3/8 F	26	DGO 1025CS
	485	475	237	13 x 20	20	CSI 08	1000	G 1/2 M	27	DGO 1320CS