


DRFB Series - Hose reel w/ safety retraction - PU/PVC hose

180° swiveling bracket
Inlet: 1 m hose
Pressure: 12 bar
Temperature: -15°C to +65°C



A (mm)	B (mm)	ID/OD (mm)	Length (m)	Coupler	Fixed inlet (mm)	Flow rate (l/min)	Weight (kg)	Parts Numbers
340	302	8 x 12	12	BSI 06	8 x 12	500	6	DRFB 0812BS
370	337	8 x 12	15	BSI 06	8 x 12	350	7	DRFB 0815BS
340	302	10 x 14	10	BSI 06	10 x 14	750	5.7	DRFB 1010BS
370	337	10 x 14	12	BSI 06	10 x 14	750	6.8	DRFB 1012BS
340	302	8 x 12	12	ESI 07	8 x 12	500	6	DRFB 0812ES
370	337	8 x 12	15	ESI 07	8 x 12	350	7	DRFB 0815ES
340	302	10 x 14	10	ESI 07	10 x 14	900	5.7	DRFB 1010ES
370	337	10 x 14	12	ESI 07	10 x 14	800	6.8	DRFB 1012ES
340	302	8 x 12	12	ISI 06	8 x 12	500	6	DRFB 0812IS
370	337	8 x 12	15	ISI 06	8 x 12	350	7	DRFB 0815IS
340	302	10 x 14	10	ISI 06	10 x 14	833	5.7	DRFB 1010IS
370	337	10 x 14	12	ISI 06	10 x 14	800	6.8	DRFB 1012IS
340	302	8 x 12	12	CSI 06	8 x 12	500	6	DRFB 0812CS
370	337	8 x 12	15	CSI 06	8 x 12	350	7	DRFB 0815CS
340	302	10 x 14	10	CSI 06	10 x 14	833	5.7	DRFB 1010CS
370	337	10 x 14	12	CSI 06	10 x 14	800	6.8	DRFB 1012CS
340	302	8 x 12	12	ASI 06	8 x 12	500	6	DRFB 0812AS
370	337	8 x 12	15	ASI 06	8 x 12	350	7	DRFB 0815AS
340	302	10 x 14	10	ASI 06	10 x 14	800	5.7	DRFB 1010AS
370	337	10 x 14	12	ASI 06	10 x 14	800	6.8	DRFB 1012AS