

## DLO series - Extra large - Rubber hose



### Technical characteristics

**Technology:** Pipe locked with ratchet stop

**Max operating pressure:** 12 bar

**Construction:** Epoxy-coated steel case

**Connection:** 1 m of inlet supply hose

**Equipped with:** Fixed bracket

Fixed bracket


Inlet: Male G 1/2 M

Inlet: Male G 1 M for DLO 1920

+ 1 m hose

Pressure: 12 bar

Temperature: -15°C to +70°C

	A (mm)	B (mm)	ID/OD (mm)	Length (m)	Coupler	Flow rate (l/min)	Swivel inlet BSPP male thread	Weight (kg)	Parts Numbers
	615	610	13 x 20	30	ESI 11	850	G 1/2	39	<b>DLO 1330ES</b>
	615	610	16 x 23	25	ESI 11	1700	G 1/2	39	<b>DLO 1625ES</b>
	615	610	19 x 27	20	ESI 11	2400	G 1	42	<b>DLO 1920ES</b>
	615	610	13 x 20	30	ISI 11	850	G 1/2	39	<b>DLO 1330IS</b>
	615	610	16 x 23	25	ISI 11	1700	G 1/2	41	<b>DLO 1625IS</b>
	615	610	19 x 27	20	ISI 11	2400	G 1	42	<b>DLO 1920IS</b>